

MATERIAL SAFETY DATA SHEET

Product Name: SUPER CATALYST II

SECTION 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufacturer/Supplier: Endura Manufacturing Co. Ltd.
12425 - 149 Street
Edmonton, Alberta
T5L 2J6
(Ph: (780) 451-4242 Fax: (780) 452-5079

24-Hour Emergency Number:... (613) 996-6666 (Canutec)
Product Name:..... SUPER CATALYST II
Item Number:..... UN 1263 Cl 3 PG II
Chemical Family:..... Ketones, Organotin
Material Use:..... Accelerates drying of coating.

SECTION 02: COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	C.A.S.	LD/50, ROUTE, SPECIES	LC/50, ROUTE, SPECIES	TLV	% WT
dibutyltin dilaurate	77-58-7	>2 g/kg o-r >2 g/kg d-rbt	N/A	0.1 mg/m ³	1 - 5
2,4-pentanedione	123-54-6	55 mg/kg o-r	N/A	20 ppm	75 - 100
legend: o=oral r=rat d=dermal i=inhalation rbt=rabbit fr=female rat p=intraperitoneal					

SECTION 03: HAZARDS IDENTIFICATION

Eye Contact:.... Moderately irritating to eyes and can cause tissue damage.
 Skin Contact:.... Low toxicity by skin absorption, but extended contact can cause irritation and dermatitis.
 Inhalation:..... Vapors are of low to moderate toxicity when inhaled and are irritating to nose, throat and other respiratory passages, especially in higher concentrations. Extended exposure can cause headaches, dizziness, nausea or even loss of muscular control and coordination, narcosis or unconsciousness.
 Ingestion:..... Liquid is of low to moderate toxicity when ingested, but can be hazardous if aspirated into lungs during swallowing or vomiting.
 Additional Information:..... Chronic hazards include narcosis, specific organ damage, permanent brain and nervous system damage or coma if extensively abused.

SECTION 04: FIRST AID MEASURES

Inhalation (acute):..... Remove to fresh air and if necessary restore breathing by giving artificial respiration. Administer oxygen if victim is breathing with difficulty. GET IMMEDIATE MEDICAL HELP.
 Ingestion:..... DO NOT INDUCE VOMITING. Seek medical help. Give 1 or 2 glasses water or milk, BUT ONLY IF VICTIM IS CONSCIOUS.
 Eye Contact:..... Check for and remove any contact lenses. Flush eyes IMMEDIATELY with water for 15 minutes and get immediate medical help.
 Skin Contact:..... Wash with soap and water. Clean contaminated clothing before reuse.
 Notes to Physician:..... Treatment is symptomatic. There is no specific antidote. See list of ingredients.

MATERIAL SAFETY DATA SHEET

Product Name: SUPER CATALYST II

SECTION 05: FIRE FIGHTING MEASURES

Flash Point (°C), (TCC):..... 35
 Auto Ignition Temperature (°C): N/A
 Upper Explosive Limit (% Vol):... 11.4
 Lower Explosive Limit (% Vol):..... 2.4
 Extinguishing Media:..... CO₂, dry chemical, foam. Avoid using water except as a fog.
 Hazardous Combustion Products:..... CO, CO₂. May generate toxic or irritating products. Tin oxides. Organic acid vapors.
 Sensitivity To Mechanical Impact:..... None
 Sensitivity To Static Discharge:..... Can ignite vapors.
 Special Fire Fighting Procedures:..... Wear self-contained breathing apparatus and full protective clothing. Extreme heat may cause pressure build-up in containers and possibly explosion, therefore use water to keep containers cool.
 Conditions of Flammability:..... Sparks, open flame, static discharge or extreme temperature.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Leak / Spill and Clean up:..... Remove all sources of ignition. The product should be contained and absorbed with inert materials and placed into a container. Do not seal the containers until any gas which might form has done so.

SECTION 07: HANDLING AND STORAGE

Handling Procedures:..... Avoid static charges, sparks, flames and excessive heat. Keep containers tightly closed and upright when not in use. Do not allow contact with skin or eyes, and don't breathe vapors. Electrical and mechanical equipment should be explosion-proof.
 Storage Needs:..... Store in a cool, dry place away from oxidizing agents and sources of ignition. Protect from exposure to light.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

PROTECTIVE EQUIPMENT

Eye/Type:..... Personnel should wear liquid chemical goggles or a full face shield.
 Respiratory/Type:..... Personnel should wear a suitable air supplied respirator.
 Gloves/Clothing/Footwear/Type: Personnel should wear chemical-resistant clothing, gloves and footwear.
 Other/Type:..... A safety shower and eye wash facility should be available.
 Ventilation Requirements:..... Adequate ventilation must be assured to prevent the accumulation of dangerous amounts of vapor or mist.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Physical State (appearance):... Clear yellow liquid
 Odor:..... Unpleasant
 Density (g/ml):..... 1.00
 Odor Threshold (ppm):..... N/A
 Vapor Pressure (@20°C):..... 6.9 mm Hg
 Vapor Density (Air=1):..... 3.5 - 21.7
 Evaporation Rate:..... 0.75
 Boiling Point (°C):..... 140
 pH:..... N/A
 Solubility in Water (% W/W):... N/A
 Coefficient of Water/Oil Distribution: N/A
 Freezing Point (°C):..... N/A
 Melting Point (°C):..... N/A
 VOC:..... 1002 g/l or 8.35 lbs/gal

MATERIAL SAFETY DATA SHEET**Product Name:**

SUPER CATALYST II

SECTION 10: STABILITY AND REACTIVITY

Incompatibility:.....

Reactivity Conditions:..... Oxidizing materials. Product is otherwise stable.

Conditions to avoid:..... Under oxidation conditions, peroxides may be formed. Keep away from alkalis, oxidizers.

SECTION 11: REGULATORY INFORMATION

WHMIS Classification:..... B-2, D-1A, D-2B

SECTION 12: DISPOSAL CONSIDERATIONS

Waste Disposal:.....

Dispose of waste according to local, provincial and federal regulations. Utilize authorized centers for disposal of combustible chemical material.

SECTION 13: TRANSPORT INFORMATION

T.D.G. Classification:.....

Shipping name: Paint. UN 1263, CI 3, PG II.

SECTION 14: OTHER INFORMATION

Note:.....

Prepared By:..... Endura – Information Systems

Revision Date:..... August 13, 2009